Smart cabling

Sennheiser Communications provides a smart, flexible and future-proof universal headset solution. The Easy Disconnect system allows the headset to be connected to or disconnected from the bottom cable quickly and without hassle.



The Smart Cable system allows the headset to plug into any source of communication.

If you update the telephone system, simply connect with the correct headset cable. You only need to change the bottom cable - not the headset itself.

UI 700-series

For even greater comfort and ease of use connect the headset via one of the UI (Universal Interface) boxes. All boxes facilitate convenient switching between handset and headset.



The new UI 760 in smart design and with Sound Clarity System[™] is the ideal support for using a headset. The technology effectively filters out background noise and at the same enhances the caller's voice.

If you wish to integrate a PC into the system, you can easily switch back and forth between your telephone and your PC.





www.senncom.com

Sennheiser Communications A/S Langager 6 · DK-2680 Solrød Strand · Denmark

Phone: +45 56 18 00 00 Fax: +45 56 18 00 99 Email: info@senncom.com Web: www.senncom.com



SH-series

BW-series

ActiveGard™

An active quard for your

During the course of a day, headset users may be exposed to hazardous incoming noises that can be dangerous to the hearing. A sudden high-pitched acoustic burst can be more than frightening – it can actually cause irreversible damage and pain.

To safeguard users from these imminent dangers, all Sennheiser Communications telecom headsets are equipped with innovative ActiveGard™ technology – a safety feature unique to Sennheiser Communications.





	Contact Centers / Offices							SOHO's / Small office and home use								Office wireless		
Product name	CC 510	CC 513	CC 515	CC 520	CC 530	CC 540 / CC 550	SH 300	SH 230	SH 250	SH 310	SH 330	SH 333	SH 335	SH 350	BW 900 EU	BW 900 UK	BW 900 US	
Art. no.	05357	500767	500215	05358	05359	05360 / 05361	502177	500222	500223	05352	05354	500766	500631	05356	500749	500750	500751	
Туре	Headband monaural	Neckband monaural	Headband monaural	Headband binaural	2-in-1 headband and ear clip monaural	Headband binaural	Over-the-ear monaural Choice of wearing on left or right ear	Headband monaural	Headband binaural	Ear clip monaural	Headband monaural	Neckband monaural	Headband monaural	Headband binaural	Wireless over-the-ear monaural Choice of wearing on left or right ear			
Microphone	Ultra noise canceling	Ultra noise canceling	Ultra noise canceling	Ultra noise canceling	Ultra noise canceling	Ultra noise canceling	Noise canceling	Omni directional	Omni directional	Noise canceling	Noise canceling featuring Adaptive Intelligence							
Frequency	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	
Sensitivity	-34 dB V/Pa	-34 dB V/Pa	-34 dB V/Pa	-34 dB V/Pa	-34 dB V/Pa	-34 dB V/Pa	-34 dB V/Pa	-34 dB V/Pa	-34 dB V/Pa	-34 dB V/Pa	-34 dB V/Pa	-34 dB V/Pa	-34 dB V/Pa	-34 dB V/Pa	-34 dB V/Pa	-34 dB V/Pa	-34 dB V/Pa	
Speaker	Regular ø 42 mm	Regular ø 42 mm	X-large ø 51 mm	Regular ø 42 mm	Regular ø 42 mm	46 mm / 51 mm	Two side open ø 20 mm	Regular ø 42 mm	Large ø 46 mm	Regular ø 42 mm	Regular ø 42 mm	Regular ø 42 mm	Regular ø 42 mm	Regular ø 42 mm	Open ø 20 mm	Open ø 20 mm	Open ø 20 mm	
Frequency	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	100-3.400 Hz	
Impedance	300 Ω	300 Ω	300 Ω	300 Ω	300 Ω	300 Ω	300 Ω	300 Ω	300 Ω	300 Ω	300 Ω	300 Ω	300 Ω	300 Ω	300 Ω	300 Ω	300 Ω	
SPL	Max. 104 dB SPL limited by ActiveGard™						Max. 104 dB SPL limited by ActiveGard™								Max. 104 dB SPL limited by ActiveGard™			
Features	 1 m Kevlar® reinforced cable with Sennheiser proprietary Easy Disconnect Leatherette or acoustical foam ear cushions ActiveGard™ hearing protection 						 1 m Kevlar® reinforced cable with Sennheiser proprietary Easy Disconnect Acoustical foam ear cushion ActiveGard™ hearing protection 								 Wireless – Bluetooth Class 1, version 1.2 Soft rubber ear fit rings - 3 sizes 100 meter wireless range of operation 			
Accessories	Clothing clip Microphone windscreen Spersonal identification colour clips Carry bag						 Clothing clip Windscreen Storage hook 3 ear cap rings Clothing clip Microphone windscreen Storage hook Carry bag 								Optional accessories • Additional battery for infinite talktime • Mechanical handset lifter (HSL10) • Electronical headset lifter interface box (TCl01)			
Headset							9						SO		rediot design award winner 2006	9	TCIO1	